



Specification Sheet

Ferret 16 GasLink II Emissions Analyzer

Measurement	Range	Accuracy
Hydrocarbons (HC)	0-15,000 ppm	0- 150ppm \pm 4 ppm >150ppm \pm 3% of reading
Carbon Monoxide (CO)	0-15%	0-1.0% \pm 0.02 % >1.0% \pm 3% of reading
Carbon Dioxide (CO ₂)	0-20.0%	0-10.0% \pm 0.3 % >10.0% \pm 3% of reading
Oxygen (O ₂)	0-21.0%	0-2.0% \pm 0.1% > 2.0% \pm 5% of reading
Nitric Oxide (NO _x)	0-5000 ppm	0-500ppm \pm 20 ppm > 500ppm \pm 4% of reading
Gas Response Time	<10 Seconds for reaching 90% of step changes	
Tachometer	0-3000 RPM	

Dimensions	English	Metric
Size	11 x 13 x 3.5 inches	28 x 33 x 9 cm
Shipping Weight	16 lb.	7.3 kg
Power Lead	14 feet	4.3 m
Tachometer Lead	14 feet	4.3 m
Temperature Lead	10 feet	3.0 m
Sampling Hose	25 feet	6.0 m

Environmental

Storage Temperature	-20° to 130° F	-29° to 54° C
Operating Temperature	35° to 120° F	2° to 49° C
Humidity	0 to 90% non-condensing	

Power Requirements 12v DC, Optional 120v AC adapter

Manufacturer: Made in the USA by GxT, Inc.